

90 mm

Pytes

Battery Model	V5°α Plus
Battery Cell Type	Rechargeable Li-ion Battery
Operating Voltage Range	47.5Vd.c.~57.6Vd.c.
Nominal Voltage	51.2Vd.c.
Rated Energy	5.12kWh
Rated Capacity	100Ah
Rated Charge/Discharge Current	50A
Recommended Charge/Discharge Current	75A
Recommended Charge/Discharge Power	3840W
Protective Class	Class I
Ingress Protection Code	IP20
Short-circuit Current	2000A@80ms

CAUTION!

IFpP51/161/120[16S]E/-10+50/95

- ◆ Do not dispose of any battery in a fire. The batteries may explode.
- ◆ Do not open or mutilate any battery. Released electrolyte is harmful to the skin and eyes. It may be toxic.
- ◆ A Battery can present a risk of electric shock and burn by high short-circuit current.
- ◆ Failed batteries can reach temperature that exceed the burn thresholds for touchable surface.

S/N:

Date:



Modèle de Batterie	V5°α Plus
Type de Cellule de La Batterie	Batterie Li-ion Rechargeable
Plage de Tension de Fonctionnement	47.5Vd.c.~57.6Vd.c.
Tension Nominale	51.2Vd.c.
Énergie Nominale	5.12kWh
Capacité Nominale	100Ah
Courant Nominal de Charge/Décharge	50A
Courant de Charge/Décharge Recommandé	75A
Puissance de Charge/Décharge Recommandée	3840W
Classe de Protection	Class I
L'indice de Protection D'enveloppe	IP20
Courant de Court-circuit	2000A@80ms

ATTENTION!

IFpP51/161/120[16S]E/-10+50/95

- ◆ Ne jetez aucune batterie au feu. Les batteries peuvent exploser.
- ◆ Ne pas ouvrir ni mutiler aucune batterie. L'électrolyte libéré est nocif pour la peau et les yeux. Il peut être toxique.
- ◆ Une batterie peut présenter un risque d'électrocution et de brûlure en raison d'un courant de court-circuit élevé.
- ◆ Les batteries défectueuses peuvent atteindre une température dépassant le seuil de brûlure pour les surfaces touchables.

MADE IN CHINA (Fabriqué en Chine)

Shanghai PYTES Energy Co., Ltd.

No.3492, Jinqian Road, Fengxian District, Shanghai, 201406, China

(N° 3492, Route Jin Qian, Quartier de Fengxian, Shanghai, 201406, Chine)

www.pytesess.com

ess_support@pytesgroup.com

170 mm