



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 1 of 28
Issued: April 2, 2026
Revised: None

620 Old Peachtree Road NW, Suite 100, Suwanee, GA 30024 USA (770) 570-1800

Test Report Number: SHES250901811431

A representative sample of the product covered by this report has been evaluated and found to comply with the applicable requirements of

- Energy Storage Systems and Equipment – ANSI/CAN/UL 9540:2023, Third Edition, dated June 28, 2023

Issuing Laboratory	SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.
Address.....	588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China
Applicant (Certificate Holder)	Shanghai PYTES Energy Co., Ltd.
Address.....	No. 3492 Jinqian Road, Qingcun Town, Fengxian District, Shanghai, 201400, China
Contact Details	Zhang Lin Phone: +86 13104603326 E-mail: lin_zhang_lz@pytesgroup.com
Manufacturer	Shanghai PYTES Energy Co., Ltd.
Address.....	No. 3492 Jinqian Road, Qingcun Town, Fengxian District, Shanghai, 201400, China
Contact Details	Zhang Lin Phone: +86 13104603326 E-mail: lin_zhang_lz@pytesgroup.com
Factory	Shanghai PYTES Energy Co., Ltd.
Address.....	No. 3492 Jinqian Road, Qingcun Town, Fengxian District, Shanghai, 201400, China
Contact Details	Zhang Lin Phone: +86 13104603326 E-mail: lin_zhang_lz@pytesgroup.com

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Product Type	DC Energy Storage System
Trademark	PYTES
Product description	The products covered by this report are permanently connected DC Energy Storage System for use in household or electric power systems. The units are suitable for installation in indoor / outdoor locations. The installation should be in accordance with the National Electrical Code, NFPA 70 and Installation of Stationary Energy Storage Systems, NFPA 855.
Model Number(s)	V5° ESS, V5°α ESS
Model Differences	All models have identical mechanical and electrical construction. The model difference between V5° ESS and V5°α ESS is the model of DC output connectors.
Electrical Ratings	V5° ESS includes Batteries of V5° (Up to 96 in parallel) and Battery Boxes or Brackets. Battery Type LFP, Battery Voltage Range 47.5Vdc~57.6Vdc, Max Charge / Discharge Current 75A*n (n for parallel quantity, 1~96), Max Energy Output 5.12kWh*n (n for parallel quantity, 1~96), Charge Temperature 0~57°C, Discharge Temperature -18~57°C, 6000 cycles. V5°α ESS includes Batteries of V5°α (Up to 96 in parallel) and Battery Boxes or Brackets. Battery Type LFP, Battery Voltage Range 47.5Vdc~57.6Vdc, Max Charge / Discharge Current 75A*n (n for parallel quantity, 1~96), Max Energy Output 5.12kWh*n (n for parallel quantity, 1~96), Charge Temperature 0~57°C, Discharge Temperature -18~57°C, 6000 cycles.
Other Ratings	IP55 for Batteries with battery box V-BOX-OC, NEMA 3 for Batteries with battery box V-BOX-NEMA3, IP20 for Batteries with other battery boxes or brackets.
Accessories	Battery Box or Bracket(Optional):V-BOX-OC, V5°Bracket, V-BOX-N3, V-BOX-IC se, V-BOX-IC, V-BOX-NEMA3, HV48100 12S Cabinet, VR-BOX-IC, V5 BK1, V5 BK2, V-BOX-OC Plus, V-BOX-IC Plus, HV48100 15S Bracket, HV48100 15S Cabinet, refer to Photographs and Critical Components below for details.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 3 of 28
Issued: April 2, 2026
Revised: None

Testing Laboratory	Suzhou Institute of Product Quality Supervision and Inspection
Address.....	2/F North C, Building 2, No.50, North Guandu Road, Wuzhong District, Suzhou, Jiangsu, China
Date of receipt of test item.....	2025-10-15
Date(s) of performance of tests	2025-10-20 to 2025-10-24
Certification Conditions	
(X Condition)	The DC Energy Storage System is to be installed in accordance with the National Electrical Code NFPA 70 (National Electric Code) or CSA C22.1 (Canadian Electric Code) and Installation of Stationary Energy Storage Systems, NFPA 855 by end user.
Component Conditions	
(U Condition)	N/A

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 4 of 28
Issued: April 2, 2026
Revised: None

CO-LISTING PAGE

CO-LISTING APPLICANT I

Applicant's Name:

Address:

Primary Contact:

Phone:

Email:

Product Correlation:

Basic Models	Co-Listed Models	Note any differences between Basic and Co-Listed models

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 5 of 28
Issued: April 2, 2026
Revised: None

CO-LISTING APPLICANT II

Applicant's Name:

Address:

Primary Contact:

Phone:

Email:

Product Correlation:

Basic Models	Co-Listed Models	Note any differences between Basic and Co-Listed models

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

GENERAL INFORMATION**Components**

Components used in the covered products must be those outlined in the latest edition of the Listing Report.

Listing Marking

This report along with a valid certificate authorizes the certificate holder to use the Listing Marking of SGS North America only on products covered by this report and in accordance with the Product Certification Program Policy Handbook.

Production Line Tests

Manufacturing and Production Tests shall be performed as required by this Report.

Responsibility of the Manufacturer and Factory

- 1) It is the manufacturer and factory's responsibility to restrict the use of markings which reference SGS to those products which are found by the manufacturers own inspection to comply with the product description in this report. This includes reference to SGS directly and/or indirectly.
- 2) During hours in which the factory is in operation, the SGS inspector shall be given unlimited access to any portion of the premises where the product and/or parts are being produced, assembled, inspected and labeled; and to the test area designated for routine tests. The SGS inspector shall be permitted to inspect and subject the products to prescribed tests prior to shipment any product bearing or intended to bear marking referencing SGS.
- 3) The factory shall provide all required testing equipment and facilities including trained personnel for conducting all routine tests that are to be performed at the factory. These shall be available when needed so that the inspection work can proceed without delays.

Follow up Inspections

As part of the SGS Follow-Up inspection, it is required that an inspector periodically visit the factory location(s) and select for examination and/or testing, the most recent production sample of the product covered in the Listing Report.

SGS Inspector

- 1) A product which is found by the SGS inspector to have features which make it unacceptable to bear marking referencing SGS shall be corrected if the listing marking is to be used. The inspector shall carefully check additional production for such features until conditions are considered normal.
- 2) A product which does not comply with the provisions of the listing report shall have all reference to SGS removed. If the rejection of the product is questioned by the factory representative, it may be put on hold in separate area of location pending appeal. The factory shall satisfy the inspector that all marks referencing SGS are removed from the rejected material or finished product. Factory shall destroy product and or turn over to inspector for destruction.
- 3) All discrepancies between the product and the listing report shall be immediately stated to the attention of the factory representative. This shall be noted in the follow-up inspection report as a discrepancy.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

GENERAL CONSTRUCTIONAL REQUIREMENTS TO BE VERIFIED

Construction Details - This section specifies construction and component details in addition to the critical components table which are to be verified during factory follow-up inspections.

1. Mechanical Assembly – A wiring device shall be prevented from any turning that can apply tension to conductor connections, result in damage to the conductor, or otherwise adversely affect the assembly. Friction alone between the mating parts of the assembly shall not be acceptable to prevent turning.
2. Corrosion – All bare metal parts are protected against corrosion by coating, painting, plating or other means specifically identified in the specific construction details unless these metal parts inherently possess such properties to resist corrosion.
3. Accessibility of Live Parts – All uninsulated live parts in primary circuitry are housed within a metallic enclosure constructed without openings unless otherwise described in the construction details.
4. Grounding – All dead-metal parts external or within the enclosure that are exposed to contact during normal or any servicing operation are connected to the equipment grounding terminal. The methods of protective bonding and grounding of an ESS shall be in accordance with Article 250 of NFPA 70 or Section 9 of IEEE C2 as applicable to where the system is located. When sizing the protective bonding and grounding wire, the rating and fault current path of all sources of supply connected to the equipment or system shall be considered. In Canada, the methods of bonding and grounding of an ESS shall be in accordance with Section 10 and 36 of CSA C22.1.
5. Conductor Protection - Conductors that pass over edges or through openings in metal shall be secured from contacting the edges or be protected from cutting and abrasion. For sheet metal less than 1.1 mm thick, protection shall be provided by one of the following methods:
 - (a) rolling the edge of the metal not less than 120 degrees;
 - (b) a bushing or grommet of a material other than rubber at least 1.2 mm thick; or
 - (c) glass sleeving at least 0.25 mm thick.
6. Internal Wiring – UL/CUL listed. Internal wiring shall be routed, supported, clamped or secured in a manner that reduces the likelihood of excessive strain on wire and on terminal connections; loosening of terminal connections; and damage of conductor insulation.
7. Wire Connectors – UL/CUL listed of UL486A-486B.
8. Heat Shrinkable Tubing – UL recognized of materials, covered on wire connectors.
9. Marking and Labeling Systems – Pressure-sensitive labels and nameplates of the permanent type (Type P) that are secured by adhesive shall be in accordance with CSA C22.2 No. 0.15 or UL 969, suitable for damp locations and rated min. 60 °C when applied on Canopy.
10. Installation, Operating and Safety Instructions – Instructions for installation and use of this product are provided by the manufacturer as required by the standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 8 of 28
Issued: April 2, 2026
Revised: None

11. Opening and/or knockout – Opening and/or knockout for conduit or armored cable will be provided in field, then suitable conduit hubs shall be used to guarantee minimum 12.7mm spacing to wall shall be guaranteed.
12. Field wiring – The field wiring for different part of system will not be provided by Manufacturer, so suitable wire size and number shall be chosen according to National Electrical Code, NFPA 70, the Canadian Electrical Code, Part I Safety Standard for Electrical Installations, C22.1, or the National Electrical Safety Code, IEEE C2 as applicable to where the system is located.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

ROUTINE TESTS FOR MANUFACTURING AND PRODUCTION

The manufacturer shall perform the following Manufacturing and Production Tests on 100% of equipment produced which has both hazardous live parts and accessible conductive parts.

Required Tests

Dielectric Voltage Withstand Test
Grounding Continuity Test
Check of Safety Controls

Dielectric Voltage Withstand Test

A dielectric withstand test as outlined in the Dielectric Voltage Withstand Test in Section 32 shall be conducted on 100 % production of ESS with working voltage exceeding 60 Vdc or 30 Vrms/42.4 Vpeak.

Section 32:

The dielectric voltage withstand test is an evaluation of the electrical spacings and insulation associated with the hazardous voltage circuits within the DUT.

Circuits at 42.4Vpeak / 30Vrms or 60Vdc or higher shall be subjected to a dielectric withstand voltage in accordance with the "Determining clearances using required withstand voltage" clause of UL 62368-1/CSA C22.2 No. 62368-1.

Exception No. 1: Semiconductors or similar electronic components liable to be damaged by application of the test voltage shall be bypassed or disconnected.

Exception No. 2: The dielectric voltage withstand test need not be conducted on integral ESS, fuel cells, and inverter systems, etc. that have already been evaluated in accordance with their individual standard requirements. Only those electrical parts external to the tested systems and their connections not previously evaluated need to be tested.

The voltage applied during the dielectric voltage withstand test is to be applied between the hazardous voltage circuits of the DUT and accessible non-current carrying conductive parts.

The voltage applied during the dielectric voltage withstand test is also to be applied between the hazardous voltage charging circuit and the enclosure/accessible non-current carrying conductive parts of the DUT.

The voltages applied during the dielectric voltage withstand test shall be applied for a minimum of 1 min.

The test equipment shall consist of a 500VA or larger capacity transformer, the output voltage, which is variable and which is essentially sinusoidal if using ac test method, a dc output if using a dc test method. There is no trip current setting for the test equipment since the test is checking for insulation breakdown, which results in a large increase of current. Setting a trip current may result in a false failure of this test, as it is not necessarily indicative of insulation breakdown.

Exception: A 500VA or larger capacity transformer need not be used if the transformer is provided with a voltmeter that directly measures the applied output potential.

There shall be no evidence of a dielectric breakdown (breakdown of insulation resulting in a short through insulation/arcing over electrical spacings) as evidenced by an appropriate signal from the dielectric withstand test equipment as a result of the applied test voltage. Corona discharge or a single momentary discharge is not regarded as dielectric breakdown (i.e. insulation breakdown).

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Exception No. 1: The time for the production Dielectric Withstand Test can be reduced to 1s.

Exception No. 2: Testing can be conducted on subassemblies of the system.

Exception No. 3: Testing can be waived if conducted as part of the specific technology evaluation (i.e. tested per UL 1973, etc.).

Grounding Continuity Test

Method

The grounding and bonding system of an ESS shall be subjected to a check using an impedance measuring device. The measurements shall occur between any two locations of the grounding and bonding system.

No resistance measurements of the grounding and bonding system shall exceed 0.1Ω or if using the test method in (d), the compliance criteria shall be in accordance with IEC 60364-4-41.

The impedance of the system grounding and bonding circuit shall be determined using one of the following methods:

- a) The circuit between the grounding terminal and the part to be grounded is measured using impedance measuring equipment;
- b) In accordance with the Continuity of the Equipment Grounding Circuit section, Section 18.2 of NFPA 79 (voltage drop measurement of the circuit using a 10 A low voltage supply source); or
- c) In accordance with test in the "Resistance of the Protective Bonding System" clause, Clause 5.6.6 of UL 62368-1/CSA C22.2 No. 62368-1 (measuring voltage drop in circuit using a low voltage supply source providing a current based upon circuit protection rating).
- d) The fault loop impedance measurement in accordance with IEC 60364-4-41.

In Canada, the circuit under test is referred to as the bonding circuit per CSA C22.1.

Exception: This testing can be waived if it is determined that the ESS construction and production methods to ensure good grounding and bonding of the system production can be determined through a review of production practices. However, if any point of the grounding system is maintained through a single fastener, a ground bond test shall be conducted.

Check of safety controls

Energy storage systems shall be subjected to 100% production screening to determine that any active controls utilized for safety are functioning.

Exception: This check of the safety controls can be conducted on subassemblies or components of the system before final assembly

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 11 of 28
Issued: April 2, 2026
Revised: None

PHOTOGRAPHS

DC Energy Storage System
V5° ESS, V5°α ESS

Photo 1: Battery Module V5°



Photo 2: Battery Module V5°α



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 3: Battery Box (V-BOX-OC)





Photo 4: Battery Bracket (V5° Bracket)




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 5: Battery Box (V-BOX-N3)



Photo 6: Battery Box (V-BOX-IC se)



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 7: Battery Box (V-BOX-IC)



Photo 8: Battery Box (V-BOX-NEMA3)




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 9: Battery Box (HV48100 12S Cabinet)



Photo 10: Battery Box (VR-BOX-IC)



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 11: Battery Bracket (V5 BK1)





Photo 12: Battery Bracket (V5 BK2)



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 13: Battery Box (V-BOX-OC Plus)



Photo 14: Battery Box (V-BOX-IC Plus)




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Photo 15: Battery Box (HV48100 15S Cabinet)



Photo 16: Battery Bracket (HV48100 15S Bracket)



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

CRITICAL COMPONENTS

The following components are considered "critical" in terms of this certification and must be verified during factory inspections. No substitutions or alternate components are allowed unless specifically as stated in this report.

Photo No.	Item No.	Component name	Manufacturer / trademark	Type/model	Technical data	Standard	Mark(s) of conformity
1	1	Battery Module	Pytes	V5°	Nominal Capacity 100Ah (5.12kWh), Operating Voltage Range 47.5Vdc~57.6Vdc, Recommended Charge/ Discharge Current 75A, Charge Temperature 0~57°C, Discharge Temperature -18~57°C, 6000 cycles.	CAN/UL 1973:2022	cTUVus (Certificate No.: U10 003364 0018 Rev.00)
2	2	Battery Module	Pytes	V5°α	Nominal Capacity 100Ah (5.12kWh), Operating Voltage Range 47.5Vdc~57.6Vdc, Recommended Charge/ Discharge Current 75A, Charge Temperature 0~57°C, Discharge Temperature -18~57°C, 6000 cycles.	CAN/UL 1973:2022	cTUVus (Certificate No.: U10 003364 0018 Rev.00)
3	3	Battery Box	Pytes	V-BOX-OC	645mm*395mm*1395mm, 4 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
4	4	Battery Bracket	Pytes	V5° Bracket	50mm*177.8mm*62.2mm each piece, 4 pieces as a set to hold one Battery Module, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
5	5	Battery Box	Pytes	V-BOX-N3	521.5mm*403.9mm*647.4mm, 2 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
6	6	Battery Box	Pytes	V-BOX-IC se	533mm*565mm*650mm, 3 Battery Modules / Box, Galvanized square tube steel & SPCC	ANSI/CAN/UL 9540:2023	Tested with appliance
7	7	Battery Box	Pytes	V-BOX-IC	533mm*611mm*650mm, 3 Battery Modules / Box, Galvanized square tube steel & SPCC	ANSI/CAN/UL 9540:2023	Tested with appliance

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 20 of 28
Issued: April 2, 2026
Revised: None

8	8	Battery Box	Pytes	V-BOX-NEMA3	521.5*403.9*647.4mm, 2 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
9	9	Battery Box	Pytes	HV48100 12S Cabinet	With Wheels: 595mm*680mm*2082mm, No Wheel: 595mm*680mm*1980mm, 13 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
10	10	Battery Box	Pytes	VR-BOX-IC	681mm*341mm*851mm, 2 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
11	11	Battery Bracket	Pytes	V5 BK1	Upper bracket: 27mm*92mm*145mm, Lower auxiliary bracket: 48mm*50mm*60mm, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
12	12	Battery Bracket	Pytes	V5 BK2	Upper bracket: 27mm*87mm*291mm, Lower bracket: 53mm*50mm*60mm, Connection Board: 27.5mm*60mm*100mm, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
13	13	Battery Box	Pytes	V-BOX-OC Plus	655mm*395mm*1416mm, 4 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
14	14	Battery Box	Pytes	V-BOX-IC Plus	533mm*611mm*650mm, 3 Battery Modules / Box, SGCC	ANSI/CAN/UL 9540:2023	Tested with appliance
15	15	Battery Box	Pytes	HV48100 15S Cabinet	1053*626*1465.7mm, 15 Battery Modules / Box, Galvanized square tube steel & SPCC	ANSI/CAN/UL 9540:2023	Tested with appliance
16	16	Battery Bracket	Pytes	HV48100 15S Bracket	1054mm*580mm*1470mm, Galvanized square tube steel & SPCC	ANSI/CAN/UL 9540:2023	Tested with appliance

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 21 of 28
Issued: April 2, 2026
Revised: None

ANNUAL RE-TESTING OF UNLISTED COMPONENTS

The unlisted components on this page are uncontrolled (not falling under a third party certification program) and require periodic retesting and/or evaluation.

Note to SGS Follow Up Inspector: The inspection office will notify you in writing when these components must be selected and sent to the Lab indicated below for re-evaluation.

Ship the samples to:

The unlisted components covered by this report and are required to be re-tested/evaluated are shown in the following table:

PHOTO #	ITEM #	DESCRIPTION	MFR	TYPE/ MODEL	RATING
VERIFICATION PROCESS					
Test Standard:					
Frequency of Testing:		No. of Test Samples:			
Clause No.	TEST		PARAMETERS		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

MARKINGS

The following markings are required:

Copy of marking plate:



DC Energy Storage System

V5° ESS

Battery Type	LFP
Battery Voltage Range	47.5Vd.c.-57.6Vd.c.
Battery Max. Charge/Discharge Current	75A*n
Battery Maximum Energy Output	5.12kWh*n
Duty cycle	6000 Cycles
Standard Charge Temperature	0°C - 57°C
Standard Discharge Temperature	-18°C - 57°C
Max. Weight	44kg*n
Battery Ingress Protection	IP20
Battery Ingress Protection with V-BOX-OC	IP55
Battery Ingress Protection with V-BOX-NEMA3	NEMA3
Max. Efficiency	97.5%

This system is UL 9540 certified under Test Report No.SHE5250901811431

*Suitable for Use in Residential Non-Habitable Spaces.

*The components of the system:
Battery:Pytes,V5° *(1~96)pcs

Battery Box or Bracket(Optional):V-BOX-OC, V5°Bracket, V-BOX-N3, V-BOX-IC se, V-BOX-IC, V-BOX-NEMA3, HV48100 12S Cabinet, VR-BOX-IC, V5 BK1, V5 BK2, V-BOX-OC Plus, V-BOX-IC Plus, HV48100 15S Bracket, HV48100 15S Cabinet









Product Serial Number

1. Label is attached on the side surface of enclosure and visible after installation.
2. IP55 for Batteries with battery box V-BOX-OC, NEMA 3 for Batteries with battery box V-BOX-NEMA3, IP20 for Batteries with other battery boxes or brackets.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Copy of marking plate:



DC Energy Storage System

V5^a ESS

Battery Type	LFP
Battery Voltage Range	47.5Vd.c.-57.6Vd.c.
Battery Max. Charge/Discharge Current	75A*n
Battery Maximum Energy Output	5.12kWh*n
Duty cycle	6000 Cycles
Standard Charge Temperature	0°C - 57°C
Standard Discharge Temperature	-18°C - 57°C
Max. Weight	44kg*n
Battery Ingress Protection	IP20
Battery Ingress Protection with V-BOX-OC	IP55
Battery Ingress Protection with V-BOX-NEMA3	NEMA3
Max. Efficiency	97.5%

This system is UL 9540 certified under Test Report No.SHES250901811431

*Suitable for Use in Residential Non-Habitable Spaces.

*The components of the system:
Battery:Pytes,V5^a *(1~96)pcs

Battery Box or Bracket(Optional):V-BOX-OC, V5^aBracket, V-BOX-N3, V-BOX-IC se, V-BOX-IC, V-BOX-NEMA3, HV48100 12S Cabinet, VR-BOX-IC, V5 BK1, V5 BK2, V-BOX-OC Plus, V-BOX-IC Plus, HV48100 15S Bracket, HV48100 15S Cabinet









5 min

Product Serial Number

1. Label is attached on the side surface of enclosure and visible after installation.
2. IP55 for Batteries with battery box V-BOX-OC, NEMA 3 for Batteries with battery box V-BOX-NEMA3, IP20 for Batteries with other battery boxes or brackets.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Safety Markings

 Warning! Avertissement!	 Warning! Avertissement!	 Warning! Avertissement!
 Hazardous Voltage Circuits Circuits a tension elevee	 Risk of Electric Shock or Serious Injury. Care Shall be taken when entering enclosure - Authorized personnel only. Risque de choc electrique ou de blessure grave. Faire attention en entrant dans l'enceinte - Personnes autorisees uniquement.	 To Reduce the Risk of Injury, read all instructions. Pour Prevenir les blessures, lire toutes les instructions.

DANGER

Danger! Low DC voltage inside
Danger! Arc flash & shock hazard

DANGER ! Basse Tension Continue(DC) interne
DANGER ! Risque d'arc électrique et d'électrocution

Charge the battery every six months to reach 90% SOC, in case of long-term storage.
Recharger la batterie tous les six mois jusqu'à 90% de l'état de charge (SOC) en cas de stockage prolongé.

ATTENTION!
Read the user manual carefully before connecting the wires.
Ensure the grounding connection is properly established before use.
Repairs must be performed by authorized and trained personnel only.
Keep the battery out of reach of children and pets.
Keep the battery away from open flames and flammable materials.
Avoid immersing the battery in or exposing it to water or other liquids.
Avoid exposure to direct sunlight and humid environments.
Do not dismantle the battery unless performed by qualified personnel.
Do not drop, crush, or strike the battery. Do not puncture or cut the battery with sharp objects.
Do not cover or wrap the battery.
Do not place heavy objects on or sit on the battery.
If the battery leaks, catches fire, or is damaged, switch off the breaker on DC side and stay away from the battery.
Contact your supplier immediately within 24 hours of any failure.

ATTENTION!
Lire attentivement le manuel d'utilisation avant de procéder au raccordement des conducteurs des câbles.
S'assurer de la mise à la terre est correctement établie avant toute mise en service.
Toute intervention de maintenance doit impérativement être réalisée par des techniciens certifiés et qualifiés.
Conserver la batterie hors de portée des enfants et des animaux.
Tenir la batterie à l'écart des flammes nues et des matières inflammables.
Éviter toute immersion de la batterie dans l'eau ou tout autre liquide.
Éviter toute exposition directe au soleil et aux environnements humides.
Ne pas démonter la batterie, sauf intervention par un personnel qualifié.
Ne pas laisser tomber, écraser ou heurter la batterie. Éviter tout perçage ou coupure avec des objets tranchants.
Ne pas recouvrir ni envelopper la batterie.
Ne pas placer d'objets lourds sur la batterie ni s'asseoir dessus.
En cas de fuite, d'incendie ou d'endommagement de la batterie: Couper immédiatement le disjoncteur côté continu (DC) et S'éloigner de la batterie.
En cas de dysfonctionnement, veuillez contacter votre fournisseur dans les 24 heures suivant l'incident.








Note:

- The marking is affixed to canopy. SGS NA Listed Mark shall be at least 5 mm high. Other letters should be at least 2.4 mm high.
- The "CAUTION" shall be at least 3.2mm high; The remaining letters shall not be less than 1.6mm high.
- The S/N number should be pasted on every end product, every S/N number denotes the date code or other dating of manufacture.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

ILLUSTRATIONS

The System Manual is as follows with products packaging:

User Manual DC ESS Version 1.0.

1. Safety Instructions

2. Overview

3. Installation

Install the Battery

Connect Ground Cable

Connecting the Power Cable

Connecting Communication Cable

Procedure of Starting

Shut Down the Battery

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

SUMMARY OF TEST RESULTS

The following tests were performed:

ANSI/CAN/UL 9540:2023 (Dated June 28, 2023)

<u>Section</u>	<u>Test Description</u>
13	Electrical Spacings and Separation of Circuits
22	Noise Levels
30	Normal Operations Test
32	Dielectric Voltage Withstand Test
34	Equipment Grounding and Bonding Test
35	Insulation Resistance Test
36	Electromagnetic Immunity Tests
41.2	Outdoors Installations Subject to Moisture Exposure

Results of the tests indicate the specimens conform to the test criteria that were found to be applicable.

Battery Part:

ANSI/UL1973:2022: Test Report No.64.280.23.60263.01 on September 13th, 2023, which issued by TUV SUD.
ANSI/CAN/UL 9540A: 2019: Test Report of Module Level No.CQES230800036801 on August 23rd, 2023, which issued by SGS.
ANSI/CAN/UL 9540A: 2019: Test Report of Unit Level No.CQES230900048501 on October 16th, 2023, which issued by SGS.

IP Tests: Test Report No.SUER230900061471 for battery rack on October 12th, 2023, which issued by SGS.
IP Tests: Test Report No.CN24ORYA 001 for battery rack on May 24th, 2024, which issued by TUV Rheinland.

System:

Electromagnetic Immunity tests of the system:

Test Report No. WPHM253272 on February 9th, 2026, which issued by Suzhou Institute of Product Quality Supervision and Inspection.

Noise level tests of the system:

Test Report No. WPHM253274 on February 9th, 2026, which issued by Suzhou Institute of Product Quality Supervision and Inspection.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



LISTING REPORT/INSPECTION PROCEDURE

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 27 of 28
Issued: April 2, 2026
Revised: None

REVISION TABLE

The following changes have been made to this Report:

<u>Revision No.</u>	<u>Date</u>	<u>Project No.</u>	<u>Revision prepared by</u>	<u>Page</u>	<u>Description of Change</u>
--				None	First issuance

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Shanghai PYTES Energy Co., Ltd.
PROJECT NUMBER: SH-CERT260201102

Page 28 of 28
Issued: April 2, 2026
Revised: None

CONCLUSION


Samples of the products covered by this Report have been found to comply with the applicable requirements of

- Energy Storage Systems and Equipment – ANSI/CAN/UL 9540:2023 Third Edition, dated June 28, 2023

Report Prepared by:

Report Reviewed by:

Report Reviewed and Approved by:



Bella Liu
Project Engineer



Allen Sun
Local Reviewer



Michael Tong
Global Reviewer

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/terms-and-conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <https://www.sgs.com/en/terms-and-conditions/terms-e-document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.