



DESIGN REPORT OF SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025



Name of the sample	Rechargeable Li-ion Battery System HV48100 SE		
Applicant	Shanghai PYTES Energy Co., Ltd.		
Supplier	Shanghai PYTES Energy Co., Ltd.		
Composition of the sample	Lithium Iron Phosphate: 38.3%; Graphite: 19.4%; Polyethylene: 2.2%; Copper Foil: 6.7%; Aluminum Alloy: 13.3%; Styrene-butadiene rubber (SBR): 0.8%; Carbon black: 0.4%; Poly (vinylidene fluoride) (PVDF): 0.8%; Lithium Hexafluorophosphate: 2.3%; Ethylene carbonate(EC): 5.6%; Ethyl methyl carbonate(EMC): 4.6%; Dimethyl carbonate(DMC): 5.6%		
Warranty of Design	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) Eleventh revised edition		
Design Result of SDS please see next page.			
Designer	孙超超	Approver	For and on behalf of CCIC JIANGSU CO. 中国检验认证集团江苏有限公司 华安

4

授权签字人 Authorized Signature(s)

Notes: This SDS is valid before the implementation of the Twelfth revised edition GHS.

Test is Located on: CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)

Tel: +86-519-83277160

Rechargeable Li-ion Battery System HV48100 SE

Warranty of Design: GHS (Eleventh
Revised Edition)

SAFETY DATA SHEET

SDS

No.: 250100320159336E

Date: Oct 24 2025

Version: 1.1



Section 1 Product and Company Identification

> Product Identifier

Product Name Rechargeable Li-ion Battery System HV48100 SE

> Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Relevant Identified Uses Please consult manufacturer.

Uses Advised Against Please consult manufacturer.

> Details of the Supplier of the Safety Data Sheet

Applicant Name Shanghai PYTES Energy Co., Ltd.
Application Address No.3492 Jinqian Road, Fengxian District, Shanghai, China
Applicant Post Code 201406
Applicant Telephone +86-021-57475800
Applicant Fax —
Applicant E-mail pytesess@pytesgroup.com
Supplier Name Shanghai PYTES Energy Co., Ltd.
Supplier Address No.3492 Jinqian Road, Fengxian District, Shanghai, China
Supplier Post Code 201406
Supplier Telephone +86-021-57475800
Supplier Fax —
Supplier E-mail pytesess@pytesgroup.com

> Emergency Phone Number

Emergency Phone Number +86-021-57475800

Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the eleventh revised edition):

> GHS Hazard Class

This product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev.11 (2025) Part 1.3.2.1.1]

> GHS Label Elements

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Date: Oct.24,2025

Version: 1.1

Pictogram Not applicable

Signal Word **Not applicable**

> Hazard Statements

Not applicable

> Precautionary Statements

Prevention

Do not open or disassemble.
Do not expose to high temperatures or open fire.
Do not mix with batteries of varying sizes, chemistries or types.
Avoid using external impact battery.

Response

Not applicable

Storage

Store under roof in cool, dry, well-ventilated areas.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 Composition/Information on Ingredients

Component	CAS No.	EC No.	Concentration (weight percent, %)
Lithium Iron Phosphate	15365-14-7	-	38.3
Graphite	7782-42-5	231-955-3	19.4
Polyethylene	9002-88-4	-	2.2
Copper Foil	7440-50-8	231-159-6	6.7
Aluminum Alloy	7429-90-5	231-072-3	13.3
Styrene-butadiene rubber (SBR)	9003-55-8	-	0.8
Carbon black	1333-86-4	215-609-9	0.4
Poly (vinylidene fluoride) (PVDF)	24937-79-9	-	0.8
Lithium Hexafluorophosphate	21324-40-3	244-334-7	2.3
Ethylene carbonate(EC)	96-49-1	202-510-0	5.6
Ethyl methyl carbonate(EMC)	623-53-0	433-480-9	4.6
Dimethyl carbonate(DMC)	616-38-6	210-478-4	5.6

Rechargeable Li-ion Battery System HV48100 SE

Warranty of Design: GHS (Eleventh
Revised Edition)

SAFETY DATA SHEET

SDS

No.: 250100320159336E

Date: Oct.24,2025

Version: 1.1

Section 4 First Aid Measures

> Description of First Aid Measures

General Advice	Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Skin Contact	Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
Inhalation	Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.
Protecting of First-aiders	Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

> Most Important Symptoms and Effects, both Acute and Delayed

- 1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

> Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

Section 5 Fire Fighting Measures

> Extinguishing Media

Suitable Extinguishing Media	Use water spray to extinguish fire. Cool surrounding Lithium batteries with water spray.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter or spread fire.

> Specific Hazards Arising from the Substance or Mixture

- 1 Containers may explode when heated.
- 2 Fire exposed containers may vent contents through pressure relief valves.
- 3 May expansion or decompose explosively when heated or involved in fire.

> Advice for Firefighters

- 1 As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.

Section 6 Accidental Release Measure

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Date: Oct.24,2025

Version: 1.1

> Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Ensure adequate ventilation. Remove all sources of ignition.
- 2 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 3 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

> Environmental Precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

> Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Section 7 Handling and Storage

> Precautions for Handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.
- 5 Take precautionary measures against static discharges.

> Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

Section 8 Exposure Controls/Personal Protection

> Control Parameters

Occupational Exposure Limit Values

Component	Country/Region	Limit Value - Eight Hours		Limit Value - Short Term	
		ppm	mg/m ³	ppm	mg/m ³
Graphite 7782-42-5	USA - OSHA	-	15	-	-
	South Korea	-	2	-	-
	Ireland	-	10	-	-
	Germany (DFG)	-	4	-	-

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

	Denmark	-	2.5	-	5
	Australia	-	3 (4)	-	-
Copper Foil 7440-50-8	The Netherlands	-	0.1	-	-
	Poland	-	0.2	-	-
	Latvia	-	0.5	-	1
	Germany (DFG)	-	0.01	-	0.02
Aluminum Alloy 7429-90-5	USA - OSHA	-	15	-	-
	South Korea	-	10	-	-
	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-
Carbon black 1333-86-4	USA - OSHA	-	3.5	-	-
	South Korea	-	3.5	-	-
	Ireland	-	3.5	-	7
	France	-	3.5	-	-
	Denmark	-	3.5	-	7
	Australia	-	3	-	-

Biological Limit Values

Component	Source	Biological monitoring index	Biological limits value	Sampling time	Remark
Lithium Hexafluorophosphate	SCOEL(EU)	Fluorine/urine	8mg/L	end of shift	

Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160 Determination of toxic substances in workplace air(Series effective standard)and GBZ/T 300 Determination of toxic substances in workplace air(Series standard).

> Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

> Personal Protection Equipment

- Eye Protection** Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
- Hand Protection** Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU),US F739 or AS/NZS 2161.1 standard.
- Respiratory protection** If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.



Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

Skin and Body Protection Wear fire/flame resistant/retardant clothing and antistatic boots.

Section 9 Physical and Chemical Properties

Appearance: Rechargeable Li-ion Battery System(HV48100 SE,358.4V 200Ah 71.68kWh), consists of 14 battery modules(HV48100 SE BMU,51.2V 100Ah 5.12kWh), individually packaged

Odor: No information available

Odor Threshold: No information available

pH: No information available

Melting Point/Freezing Point (°C): No information available

Initial Boiling Point and Boiling Range (°C): No information available

Flash Point (°C)(Closed Cup): Not applicable

Evaporation Rate: Not applicable

Flammability: No information available

Upper/lower explosive limits[% (v/v)]: Upper limit: No information available; Lower limit: No information available

Vapor Pressure (KPa): Not applicable

Relative Vapour Density(Air=1): Not applicable

Relative Density(Water=1): No information available

Solubility: No information available

n-Octanol/Water Partition Coefficient: No information available

Auto-Ignition Temperature(°C): No information available

Decomposition Temperature (°C): No information available

Kinematic Viscosity (mm²/s): Not applicable

Particle characteristics: No information available

Critical Temperature(°C): Not applicable

Section 10 Stability and Reactivity

Reactivity Contact with incompatible substances can cause decomposition or other chemical reactions.

Chemical Stability Stable under proper operation and storage conditions.

Possibility of Hazardous Reactions Mixtures with metallic acetylene, when heated, cause a fire or incandescence. Reacts severely with halogens, interhalogens or other strong oxidants, or causes a fire. Ultrafine powder will self-ignite in the air at room temperature.

Conditions to Avoid Incompatible materials, heat, flame and spark.

Incompatible Materials Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid. Halogen, interhalogen, strong oxidant, water and acids. Oxidants, halogen, interhalogen and mercury.

Hazardous Decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information

> Acute Toxicity

Component	CAS No.	LD ₅₀ (Oral)	LD ₅₀ (Dermal)	LC ₅₀ (Inhalation, 4h)
-----------	---------	-------------------------	---------------------------	-----------------------------------

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

Dimethyl carbonate(DMC)	616-38-6	13000mg/kg(Rat)	> 5000mg/kg(Rabbit)	No information available
Lithium Hexafluorophosphate	21324-40-3	50~300mg/kg(Rat)	275mg/kg(Rat)	No information available
Ethylene carbonate(EC)	96-49-1	10000mg/kg(Rat)	> 3000mg/kg(Rabbit)	No information available

> Skin Corrosion/Irritation

No information available

> Serious Eye Damage/Irritation

No information available

> Skin Sensitization

No information available

> Respiratory Sensitization

No information available

> Germ Cell Mutagenicity

No information available

> Carcinogenicity



ID	CAS No.	Component	IARC	NTP
1	15365-14-7	Lithium Iron Phosphate	Not Listed	Not Listed
2	7782-42-5	Graphite	Not Listed	Not Listed
3	9002-88-4	Polyethylene	Category 3	Not Listed
4	7440-50-8	Copper Foil	Not Listed	Not Listed
5	7429-90-5	Aluminum Alloy	Not Listed	Not Listed
6	9003-55-8	Styrene-butadiene rubber (SBR)	Category 3	Not Listed
7	1333-86-4	Carbon black	Category 2B	Not Listed
8	24937-79-9	Poly (vinylidene fluoride) (PVDF)	Not Listed	Not Listed
9	21324-40-3	Lithium Hexafluorophosphate	Not Listed	Not Listed
10	96-49-1	Ethylene carbonate(EC)	Not Listed	Not Listed
11	623-53-0	Ethyl methyl carbonate(EMC)	Not Listed	Not Listed

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Date: Oct.24,2025

Version: 1.1

12	616-38-6	Dimethyl carbonate(DMC)	Not Listed	Not Listed
----	----------	----------------------------	------------	------------

> Reproductive Toxicity

No information available

> Reproductive Toxicity (Additional)

No information available

> STOT-Single Exposure

No information available

> STOT-Repeated Exposure

No information available

> Aspiration Hazard

No information available

Section 12 Ecological Information

> Acute Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Copper Foil	7440-50-8	LC ₅₀ : 0.665mg/L (96h)(Fish)	EC ₅₀ : 0.02mg/L (48h)	ErC ₅₀ : 7.9mg/L (96h)
Aluminum Alloy	7429-90-5	LC ₅₀ : 1.55mg/L (96h)(Fish)	No information available	No information available

> Chronic Aquatic Toxicity

No information available

> Others

**Persistence and
Degradability
Bioaccumulative
Potential
Mobility in Soil**

No information available

No information available

No information available

**Results of PBT and
vPvB Assessment**

Lithium Iron Phosphate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Graphite does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Polyethylene does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Copper Foil does not meet the criteria for PBT and vPvB according to Regulation (EC)

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

No 1907/2006, annex XIII.
Aluminum Alloy does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Styrene-butadiene rubber (SBR) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Carbon black does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Poly (vinylidene fluoride) (PVDF) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Lithium Hexafluorophosphate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Ethylene carbonate(EC) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Ethyl methyl carbonate(EMC) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.
Dimethyl carbonate(DMC) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Section 13 Disposal Considerations

Waste Chemicals Contaminated Packaging Disposal Recommendations

Before disposal should refer to the relevant national and local laws and regulation. Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible. Refer to Waste chemicals and Contaminated packaging.

Section 14 Transport Information

Transporting Label



Marine pollutant

No

UN Number

3480

UN Proper Shipping Name

LITHIUM ION BATTERIES(including lithium ion polymer batteries)

Transport Hazard Class

9

Transport Subsidiary Hazard Class

NONE

Packing Group

The goods are packaged according to the packaging P903

Report remarks

According to United Nations Recommendations on the Transports of Dangerous Goods•Model Regulations, Lithium batteries(group) could be transported in accordance with the classification conclusions of this report when meet the requirements of UN38.3 test.



Section 15 Regulatory Information

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECL	AIIC	ENCS
Lithium Iron Phosphate	×	√	√	√	×	×	√	×	×
Graphite	√	√	√	√	√	√	√	√	×
Polyethylene	×	√	√	√	√	√	√	√	√
Copper Foil	√	√	√	√	√	√	√	√	×
Aluminum Alloy	√	√	√	√	√	√	√	√	×
Styrene-butadiene rubber (SBR)	×	√	√	√	√	√	√	√	√
Carbon black	√	√	√	√	√	√	√	√	×
Poly (vinylidene fluoride) (PVDF)	×	√	√	√	√	√	√	√	√
Lithium Hexafluorophosphate	√	√	×	√	×	√	√	√	×
Ethylene carbonate(EC)	√	√	√	√	√	√	√	√	√
Ethyl methyl carbonate(EMC)	√	√	×	√	×	√	√	×	√
Dimethyl carbonate(DMC)	√	√	√	√	√	√	√	√	√

【EINECS】 European Inventory of Existing Commercial Chemical Substances.

【TSCA】 United States Toxic Substances Control Act Inventory.

【DSL】 Canadian Domestic Substances List.

【IECSC】 China Inventory of Existing Chemical Substances.

【NZIoC】 New Zealand Inventory of Chemicals.

【PICCS】 Philippines Inventory of Chemicals and Chemical Substances.

【KECL】 Korea Existing Chemicals List.

【AIIC】 Australian Inventory of Industrial Chemicals.

【ENCS】 Japan List of Existing and New Chemical Substances.

Note

“√” Indicates that the substance included in the regulations

“×” That no data or included in the regulations

Section 16 Additional Information

Creation Date Oct.24,2025

Revision Date Oct.24,2025

Reason for Revision -



> Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 11th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the

Rechargeable Li-ion Battery System HV48100 SE

SAFETY DATA SHEET

No.: 250100320159336E

Date: Oct.24,2025

Warranty of Design: GHS (Eleventh
Revised Edition)

SDS

Version: 1.1

present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.





Terms of the Using of the Report

1. The report is issued by CCIC according to the information of the chemicals and the information of its shipping provided by the applicant (shipper or his agent).
2. According to the demand of this SDS, CCIC requires the applicant to provide true and exact sample and data.
3. Information from applicant is the key of this SDS, so CCIC will not respond for the wrong of applicant.
4. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
5. This report will be effective only after it is signed by the inspector, approver and stamped by CCIC.
6. CCIC guarantees the objectivity and fairness of this report, and carries out confidentiality obligations on business secrets such as business information, technical documents and so on.
7. The partly duplicating of this report is prohibited without the written approver of CCIC.
8. The report is invalid when anything of the following happens-illegal transfer, embezzlement, imposture, modification or tampering in any media form.
9. The authenticity of the certificate can be checked by scan the security code of this certificate.

Notes: Test is Located on: CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)

Tel: +86-519-83277160

