

E-BOX 48100R TE



Features



Scalable

- From 5.12kWh to 491.52kWh



Long-lasting

- ≥ 4000 Cycles @ 90% DoD



Safe & Reliable

- LiFePO₄ cells
- Self-designed & Field-proven BMS



Compact, Flexible and Easy Install



Wide Compatibility

CE UN38.3

E-BOX 48100R TE Specs

Electrical

Nominal Voltage	51.2V
Voltage Range	47.5V~57.6V
Nominal Capacity	100Ah
Nominal Energy	5.12kWh
Recommended Charge/ Discharge Current	50A (2.56kW dc)
Maximum Charge/ Discharge Current	100A (2.56kW dc)
Peak Discharge Current	102A (5.22kW@15s)

General

Chemistry	LFP
Communication Protocol	CAN/RS485
Dimensions (L x W x H)	440 x 620 x 117mm (2.6U) / 17.3 x 24.4 x 4.6 inch (2.6U)
Weight	51 kg / 112.5 lbs
Ambient Temperature	Charge: 0°C~45°C / 32°F~113°F Discharge: -10°C~ 50°C(14~122°F)
Round-Trip Efficiency	≥95%
Cycle Life*	≥4000Cycles

* Test Condition 0.5C, 25°C @90%DoD

Certifications

IEC62619 / CE / UN38.3